

GLOSS

CLEAR COAT

CREAT

MATTE

CLEAR COAT

UNCIK



|             | Scenix SSR Clears<br>(7030, 7031, 7032)  | <b>Createx Clear Coats</b><br>(5620, 5621, 5622)  |
|-------------|--|---|
| Resin Type  | Water-based Acrylic-Aliphatic Urethane   | Water-based Acrylic   |
| Basic Info  | <ul> <li>Industrial Strength, Exterior Architectural Coating</li> <li>Water-proof</li> <li>Extreme Chemical Resistance<br/>(SSR = Sun Screen Resistant)</li> <li>Non-Yellowing</li> <li>Available in 32oz. &amp; 1-Gallon sizes</li> </ul> | <ul> <li>Interior &amp; Light Exterior Applications</li> <li>Water Resistant</li> <li>Airbrush Friendly</li> <li>Easy to use, 1k</li> <li>Available in 2, 4, 8, 16, 32oz. &amp; 1-Gallon sizes</li> </ul> |
| Set-Up      | Activate with 4015 Cross Linker (2% per vol.), then dilute 4011 or 4012 (5 – 10%)  | Dilute 4011 or 4012 (5 – 10% per vol.)  |
| Pot-Life    | Scenix is activated for 4 hours after adding 4015.<br>May be re-activated by re-adding 4015 after 4<br>hours.  | No pot life.  |
| Application | Spray-Gun, 1.4mm<br>Mini-Gun, 1.0 – 1.2mm<br>Not recommended for airbrush<br>Brush: hair or foam   | Spray-Gun, 1.2mm<br>Mini-Gun, 0.8 – 1.0mm<br>Airbrush: 0.5mm<br>Brush: hair or foam   |
| Durability  | Industrial Grade Durability<br>Exterior Grade Architectural Use<br>High Block Resistance - will not stick to other paints<br>Excellent Mar Resistance - does not scratch easily<br>ASTM E-84 Smoke & Flame Class A Fire Rated              | Durable – best suited for art & hobby<br>For limited exposure to outdoor elements<br>Block Resistant<br>Improve Mar Resistance by adding<br>4015 Cross-Linker   |

|             | Scenix SSR Clears<br>(7030, 7031, 7032)   | <b>Createx Clear Coats</b><br>(5620, 5621, 5622)   |
|-------------|---|--|
| Performance | - Createx's most durable brand of clears  | <ul> <li>Durable, excellent for protecting artwork &amp;<br/>hobby</li> </ul>  |
|             | <ul> <li>Suitable for large-scale, long-term exterior<br/>paintjobs</li> </ul>  | <ul> <li>Excellent adhesion direct to plastic</li> </ul>   |
|             | <ul> <li>Cures to a hard coating with high block<br/>resistance</li> </ul>  | <ul> <li>Cures semi-hard. Less mar resistant compared<br/>to Scenix SSR Clears.</li> </ul>   |
|             | <ul> <li>Sandable &amp; Buffable. Polish 7030 to a high gloss clear.</li> </ul>   | <ul> <li>Scratches from sanding cannot be polished or<br/>buffed out.</li> </ul>   |
|             | - Excellent Self-leveling   | - Self-leveling  |
|             | <ul> <li>Fast Drying</li> <li>Scenix 7030 Gloss Clear is a higher gloss clear<br/>compared with 5620 Createx Gloss Clear</li> </ul> | <ul> <li>Airbrush friendly</li> <li>Brushes easy without leaving brush marks</li> </ul>  |
|             | - Compatible with all Createx Colors paints   | <ul> <li>For use with Createx Airbrush Colors,<br/>Illustration Colors, Wicked Colors &amp; Auto Air<br/>Colors. Not for top-coating <i>candy<sub>2</sub>O</i> (use 4040<br/>Bleed Checker first) or Scenix Mural &amp; Theme<br/>Paint</li> </ul> |
|             | - Excellent adhesion direct to any substrate*   |  |

\* Scenix SSR Clears & Createx Clear Coats may be applied direct to most any substrate as a transparent primer / adhesion promoter. Of the two, Scenix SSR Clear adheres better, which may help when painting hard plastics or unusual substrates that are hard to paint.

• Scenix SSR Clears & Createx Clear Coats may both be applied direct to aluminum & galvanized metal. Neither should be applied to untreated metal due to the risk of corrosion. Apply first a direct-to-metal primer such as a self-etching epoxy primer.

*Refer to Scenix SSR Clear & Createx Clear Coats Technical Data Sheet for more product information.* 

Manufactured by:



PO Box 120, 14 Airport Park Rd East Granby, CT 06026 800.243.2712 | 860.653.5505 info@createxcolors.com